



Gecko transport-/order picking rack

Dear customer,

You receive JOWI Gecko transport-/order picking rack in a new construction with the following advantages:

- A higher maximum pay load of von 400 kg
- Better running characteristics due to ball-bearing castors Ø 160 mm with cast polyurethane covering
- Better manoeuvrability due to a castor with directional lock
- Also available in double length with a maximum pay load of von 600 kg.

JOWI Gecko GE-590-2/1-24-1/1 transport-/order picking rack

standard model

Equipment:

2 L-uprights with castors

1 I-upright

24 support tubes

1 bottom shelf 682 x 590 mm, with a maximum pay load of 400 kg

1 intermediate shelf 374 x 590 mm, with a maximum pay load of 30 kg

locking system with fixing screws for support tubes

16 receivers for support tubes per upright - spacing 89 mm

diameter of the support tubes: 23 mm, usable length: 600 mm

pipe cover, solvent resistant and compatible with all common varnishes,

9 zincd cross tubes with a length of 748 mm

4 ball-bearing castors Ø 160 mm

with cast polyurethane covering

2 of which can be locked and 1 is equipped with a directional lock

Maximum pay load: on 2 support tubes: 30 kg, complete rack: 400 kg

Requirement: even load distribution without shock load

Dimensions: length: 890 mm, depth: 800 mm, height: 1.750 mm

steelconstruction, varnishing RAL 3004 purple red



JOWI Gecko GE-590-3/2-40-2/2 transport-/order picking rack

Equipment:

3 L-uprights with castors

2 I-uprights

40 support tubes

2 bottom shelves 682 x 590 mm, each with a maximum pay load of 400 kg

2 intermediate shelves 374 x 590 mm, each with a maximum pay load of 30 kg

locking system with fixing screws for support tubes

16 receivers for support tubes per upright - spacing 89 mm

diameter of the support tubes: 23 mm, usable length: 600 mm

pipe cover, solvent resistant and compatible with all common varnishes,

9 zincd cross tubes with a length of 1.444 mm

6 ball-bearing castors Ø 160 mm

with cast polyurethane covering

3 of which can be locked and 1 is equipped with a directional lock

Maximum pay load: on 2 support tubes: 30 kg, complete rack: 600 kg

Requirement: even load distribution without shock load

Dimensions: length: 1.586 mm, depth: 800 mm, height: 1.750 mm

steelconstruction, varnishing RAL 3004 purple red

